

	FG 1505	FG 2005
Characteristics		
Minimum capacities	100 x 100 mm	100 x 100 mm
Maximum capacities	1500 x 1000 mm	2000 x 1000 mm
Minimum thickness	5 mm	5 mm
Maximum thickness	40 mm	40 mm
Approximate weight	11000 Kg	12500 Kg
External dimensions L x w x h	3.3 x 4.4 x 3.1 m	4.0 x 4.9 x 3.1 m
Marking		
Marking power	800 kN	800 kN
Number of characters	10	10
Drilling		
Power	11 kW	11 kW
Spindle	SA 40	SA 40
Spindle speed	50 - 2000 RPM	50 - 2000 RPM
Drilling maxi diameter	Ø 40 mm	Ø 40 mm
Equipments		
Air conditioning in electrical cabinet	●	●
FG driver software	●	●
DSTV file import	●	●
Telemaintenance	●	●
Marking		
Countermark	●	●
Disk marking unit - 40 characters	○	○
Drilling		
Tool changing system (5 Ø)	●	●
11 kW spindle power	○	○
External lateral spraying	●	●
Central spraying	●	●
Central cooling	○	○
Pop-marking	●	●
Threaded holes	○	○
Deburring system	○	○

○ Optional ● Standard

VERNET BEHRINGER reserves the right to modify technical data without prior notice
Characteristics are given for E24 / ST37 steel