

	VP 150	VP 160	VP 180	VP 200	VP 206 S	VP 250- D
Characteristics						
Usable length	6 to 18 m	6 to 18 m	6 to 18 m	6 to 18 m	6 to 18 m	6 to 18 m
Minimum angle	35 x 35 x 4 mm	35 x 35 x 4 mm	45 x 45 x 4,5 mm	45 x 45 x 4,5 mm	45 x 45 x 4,5 mm	50 x 50 x 5 mm
Maximum angle	150 x 150 x 15 mm	160 x 160 x 17 mm	180 x 180 x 20 mm	200 x 200 x 24 mm	200 x 200 x 24 mm	250x250x25/35 mm
Carriage maxi speed	60 m/min	60 m/min	60 m/min	60 m/min	60 m/min	60 m/min
Punching						
Number of punching units	2 / 4 / 6	2 / 4 / 6	2 / 4 / 6	2 / 4 / 6	2 (3 tools each)	-
Punching power	500 kN	650 kN	800 kN	930 kN	1100 kN	-
Maximum diameter in maximum thickness	Ø 26 in 15 mm	Ø 30 in 17 mm	Ø 32 in 20 mm	Ø 30 in 24 mm	Ø 36 in 24 mm	-
Maximum diameter	Ø 32 mm	Ø 32 mm	Ø 32 mm	Ø 36 mm	Ø 36 mm	-
Marking	○	○	○	○	○	○
Possible marking power	650 or 800 kN	650 or 800 kN	650 or 800 kN	650 or 800 kN	650 or 800 kN	650 or 800 kN
Number of barrel stations	8 of 10 characters	9 of 10 characters	10 of 10 characters	11 of 10 characters	12 of 10 characters	13 of 10 characters
Drilling	-	○	○	○	○	●
Number of drilling units	-	2	2	2	2	2
Number of diameters per unit	-	3 or 4	3 or 4	3 or 4	3 or 4	3 or 4
Spindle power	-	11 kW	11 kW	11 kW	11 kW	11 kW
Maximum diameter	-	40 mm	40 mm	40 mm	40 mm	40 mm
Shearing						
Shearing power	1600 kN	2200 kN	2800 kN	4000 kN	4000 kN	5000 kN
Equipments						
Air conditioning in electrical cabinet	●	●	●	●	●	●
VP driver software	●	●	●	●	●	●
DSTV file import	●	●	●	●	●	●
Telemaintenance	●	●	●	●	●	●
Marking unit with barrel	○	○	○	○	○	○
Disk marking unit - 40 characters	○	○	○	○	○	○
Drilling	-	○	○	○	○	○
5000 kN shear	-	-	-	○	○	●
Loading system	○	○	○	○	○	○
Tilting take-off table for unloading	●	●	●	●	●	●
Motorized (4,5 m) take-off table	●	●	●	●	●	●

○ Optional ● Standard

VERNET BEHRINGER reserves the right to modify technical data without prior notice
Characteristics are given for E24 / ST37 steel



Building up the steel world...